



### Steel Jack ST Series

- SINOLIFT steel jacks are developed in accordance with the latest safety regulations. With milled rack, geared wheels and tempered parts of driving gear.
- Conforms to DIN 7355
- Suitable for lifting loads of any type.



1KG=2.2LB 1INCH=25.4MM

Model		ST-1.5	ST-3	ST-5	ST-10	ST-20
Capacity	kg	1500	3000	5000	10000	20000
Jack Height	mm	600	735	735	800	800
Claw Lowest Height	mm	70	70	80	100	95
Lifting Height	mm	300	355	355	380	340
Weight	kg	16	21	28	46	60

### Hydraulic Jack HJ Series

- The perfect choice for lifting loads to be moved on rollers.
- Provides the capability to jack-up loads that are just over 1" off the floor and also allow jacking from the top of the cylinder which extends the lifting range.
- HJ-5 & HJ-10 can be operated either vertically or horizontally and an internal pressure valve prevents jack overload -- HJ-25 can not be operated horizontally.
- Base, toe and pump assemblies swivel independently to enable precise positioning in tight quarters. Each has an integral carrying handle for easy portability.
- Meets ASME B30.1 standards.

1KG=2.2LB 1INCH=25.4MM

Model		HJ-5	HJ-10	HJ-25
Capacity	ton	5	10	25
Lifting of foot	mm	230	260	275
Lifting of Head	mm	575	650	720
Lowest of foot/head	mm	25/368	30/420	58/500



HJ-5 HJ-10 HJ-25

### Forklift Jack FJ Series



FJ04 FJ05 FJ05A

1KG=2.2LB 1INCH=25.4MM

Model		FJ04		FJ05		FJ05A	
				LOW POINT	TOP	LOW POINT	TOP
Capacity	ton	4T	4T	4T	5T	4T	5T
Lifting Range	mm	350	360	360	300	360	300
Min. Height	mm	65	65	65	415	65	415
Net Weight	kg	31.5	45		47		
Overall Dimensions	mm	665X200X440		680X210X410		770X210X410	

### Jack Stand JS-A(B) Series



JS2T JS3TA JS3TB JS6TA JS6TB JS12T

1KG=2.2LB 1INCH=25.4MM

Model	Lifting Capacity	Min. Height	Net Weight	Gross Weight	Quantity Case	Measurement	Quantity 1x20"
	ton	mm	kg	kg	pcs	cm	pcs
JS2T	275	420	5	5.4	2	19x18.5x34	2350
JS3TA	295	415	5	5.3	2	22.5x19.5x34.5	1900
JS3TB	295	425	6.4	6.8	2	22.5x19.5x35	1500
JS6TA	395	605	9.5	10	2	27.5x24.5x43	900
JS6TB	400	610	12	12.5	2	27.5x24.5x45	860
JS12T	460	720	26	28	2	33x29x53	500

### Jack Stand JS-C(D) Series



JS2TC JS3TC JS6TC JS2TD JS3TD JS6TD

1KG=2.2LB 1INCH=25.4MM

Model	Lifting Capacity	Min. Height	Net Weight	Gross Weight	Quantity Case	Measurement	Quantity 1x20"
	ton	mm	kg	kg	pcs	cm	pcs
JS2TC	275	425	5.5	5.8	2	21x19.5x34.5	1900
JS3TC	295	425	7	7.5	2	22x20.5x36	1750
JS6TC	400	610	14.5	15.5	2	30.5x27x47.5	700
JS2TD	270	360	3	3.4	2	68x28x32(10x2)	4700
JS3TD	300	430	4	4.4	2	68x28x35(10x2)	4200
JS6TD	375	570	3.6	3.9	2	66x27x45(10x1)	3500